

December 2020

THE LIFTSUPERSTORE AND ALL IT'S REGISTERED TRADE MARKS ARE PART OF THE TLS LIFT GROUP, PLEASE CALL US FOR PRODUCT INFORMATION ON COMMERCIAL AND HEAVY DUTY LIFT PRODUCTS. WWW.TLSLIFTS.COM

CONTACT US NOW WWW.LIFTSUPERSTORE.COM OR CALL 866-799-LIFT (5438)

۲

DRAIN

4 POST SERVICE LIFT -"PEGASUS" 15,000 LB. / 6.8T CAPACITY



۲

LSS4P15FD LSS4P15FDXL

CATEGORY		CLOSED FRONT FOUR POST LIGHT DUTY SERVICE LIFT
	CAPACITY	15,000 LB. (6.8T)
A	RAISED HEIGHT	75" (1905мм)
В	LOWERED HEIGHT	8 3/8" (213MM)
С	OVERALL LENGTH EXTENDED	2871/2 (7303мм)
с	OVERALL LENGTH STANDARD	260 1/2" (6617MM)
D	DECK LENGTH EXTENDED	238" (6045мм)
D	DECK LENGTH STANDARD	211" (5359мм)
E	WIDTH BETWEEN RUNWAYS	41" (1041MM)
F	RUNWAY DECK WIDTH	23" (584ММ)
G	OVERALL WIDTH FRONT/REAR	137 1/2" (3493мм)
н	MAX COLUMN HEIGHT	86" (2184MM)
	ALI CERTIFIED WITH GOLD LABEL	YES
*	AVAILABLE WITH OPTIONAL ALIGNMENT RADIUS & SLIP PLATES	YES
	MAX. WHEEL BASE EXTENDED	209" / 5309мм
	MAX WHEEL WHEEL BASE STAN- DARD	182" / 4623MM
	LIFT TIME	70 SECONDS
	POWER REQUIREMENTS	230V - 60HZ - 1PH - 25 AMP
	JACKING BEAM CAPACITY	7,500 LB. (3.4T)
	SHIPPING WEIGHT	4750 LB. (2159 KG)

Disclaimer: TLS Inc. is constantly updating their products to maintain the highest possible standards of

performance and safety. The specifications included in this brochure are only accurate at the time of

printing and are subject to change without notice

ADDITIONAL FEATURES

NORTH AMERICAN "BUCHER"

2 HP POWER UNIT

INCLUDES AIR REGULATOR

WATER TRAP OILER


FEATURES


- BUILT TO HIGHER QUALITY STANDARD; 100% NORTH AMERICAN MADE - PREMIUM US BUCHER 2HP / 1.5KW POWER UNIT.
- CORROSION RESISTANT
 PROTECTION STEEL
 COMPONENTS ARE WHEEL-A BRATOR SHOT BLASTED AND ACID
 WASHED BEFORE A "DOUBLE BAKE"
 POWDER COAT FINISH IS APPLIED.
- SUPERIOR STRUCTURAL STRENGTH PROVIDES LONGER LIFE - NON FLEX DOUBLE WALL 23" / 584MM WIDE RUNWAYS WITH BUILT IN "Z" RAIL.
 HEAVY DUTY 10" X 8 3/8" X 1/8"
 WALL / 254MM X 213MM X 3.2MM
 WALL / 254MM X 213MM X 3.2MM
 WALL COLUMNS AND 3" X 6 X 1/4"
 / 72MM X 210MM X 6.4MM TUBE TRAVERSE BEAMS.
- GREATER FLEXIBILITY WITH MORE MODELS TO CHOSE FROM - AVAILABLE IN TWO RUNWAY LENGTHS WITH BUILT IN WHEEL ALIGNMENT OR SERVICE DECK. LIFT CAN BE ORDERED IN RED OR BLUE.
- PREMIUM OPTIONS AND ACCESSORIES CAN EXPAND THE CAPABILITIES AND SERVICE LIFE - BUILT IN TIRE INFLATION HOSES, REMOVABLE WORK STEPS, LED RUNWAY LIGHTING AND PREMIUM LONG LIFE 5 YEAR WARRANTY HD JACKING BEAMS

- LOWER MAINTENANCE COSTS
 ZIRK STYLE GREASE FITTINGS AT ALL 1 1/2" / 38MM PLATED HINGE PINS.
- EXTENDED LIFE "NON TWIST" CABLE DESIGN - MACHINED STEEL NICKEL PLATED 9" / 229MM PULLEYS WITH BRONZE SELF LUBRICATING BUSHINGS. NON SPIN FATIGUE RESISTANT 1/2" / 12.3 MM CABLES ARE ROUTED ON DOUBLE STACKED PULLEYS (VERSUS FOUR STACKED) TO REDUCE STRESS AND WEAR.
- LOW PRESSURE HYDRAULICS
 PROVIDES LONGER LIFE 4" ID X 65"
 / 102MM ID X 1651MM CYLINDER IS
 MOUNTED UNDER THE RUNWAY AND
 USE A PREMIUM "PARKER" SEAL
 AND WEAR RING WITH CHROME
 PLATED PLUNGER SHAFT.
- DESIGNED FOR OPTIMUM
 PRODUCTIVITY SINGLE POINT
 CONTROL WITH STAINLESS
 STEEL CYLINDER AIR RELEASES
 ENGAGE 11 LOCKING POSITIONS.
 ADJUSTABLE LOCKING LADDERS 81"
 X 6" X 5/16" 2057MM X 70MM X 7.9
 MM THICK ALLOW FOR ACCURATE
 LEVELLING. POWER UNIT CAN
 BE MOUNTED ON A FRONT OR
 REAR COLUMN. BUILT IN RUNWAY
 COMPRESSED AIR OUTLETS FRONT
 AND REAR

 (\bullet)

EQUIPMENT FOOTPRINT





The Liftsuperstore Retail locations throughout the USA - Florida, Texas, Wisconsin, Missouri, Virginia & Alabama Call: 866-799-5438

December 2020



PREMIUM 9" (229MM) PULLEY AND CABLES 1/2" (12.3MM) CABLES



DOUBLE WALL DECK WITH Z RAIL



۲